

US006005817A

United States Patent [19]

Gudesen et al.

[11] Patent Number:

6,005,817

[45] **Date of Patent:**

Dec. 21, 1999

[54] METHOD FOR PARALLEL WRITING AND READING OF DATA IN AN OPTICAL MEMORY, A WRITING/READING DEVICE FOR USE BY THE METHOD AND USES OF THE METHOD AND THE WRITING/READING DEVICE

[75] Inventors: Hans Gude Gudesen, Gamle

Fredrikstad; Per-Erik Nordal, Nesbru,

both of Norway

[73] Assignee: Opticom ASA, Oslo, Norway

[21] Appl. No.: **08/981,661**

[22] PCT Filed: Jul. 18, 1996

[86] PCT No.: PCT/NO96/00187

§ 371 Date: **Jan. 8, 1998**

§ 102(e) Date: Jan. 8, 1998

[87] PCT Pub. No.: **WO97/04448**

PCT Pub. Date: Feb. 6, 1997

[30] Foreign Application Priority Data

Jul. 18, 1995 [NO] Norway 952855

[51] Int. Cl.⁶ G11C 7/00

[56] References Cited

U.S. PATENT DOCUMENTS

4,633,445 12/1986 Sprague.

5,436,871	7/1995	Russell .
5,479,384	12/1995	Toth et al
5,587,820	12/1996	May et al 359/72
5,696,714	12/1997	Russell

FOREIGN PATENT DOCUMENTS

WO91 11804 8/1991 European Pat. Off. . WO93 13529 4/1993 European Pat. Off. .

Primary Examiner—Huan Hoang

[57] ABSTRACT

In a method for parallel writing and reading of data in an optical memory, the optical memory includes one or more microlenses for accessing a memory medium, individually addressable elements arranged in one or two-dimensional matrices in a write/read device are activated. The activation of an element physically influences one or more localized areas in a data carrying layer in the memory for writing and reading of data carrying structures in the localized area. Writing and reading is thus performed on the basis of a relationship between the geometric location of the element in the matrix and the position of the localized area(s) in the data carrying layer of the memory. A write/read device includes individually addressable elements which are arranged in one or two-dimensional matrices, the addressable element being arranged to be activated in order to physically influence one or more of the above-mentioned localized areas. Use for such a configuration includes, for example, writing and reading in optical memories which consist of 1-100 microlenses with associated data carrying layers and in optical memories which consist of a transparent spherical particle having a transparent layer to which is applied a data carrying film arranged on one side thereof.

62 Claims, 7 Drawing Sheets

